

Description

The Digital Alarm Communicator Transmitter (DACT-E3) is an optional component of the E3 Series[®] Expandable Emergency Evacuation System. The DACT-E3 sends digital signals over the telephone network to a central station. This module can be located in the main cabinet or remotely located via a local RS-485 serial interface.

The DACT-E3 is compatible with digital alarm communicator receivers (DACRs) that receive the following signaling formats:

- SIA DC8
- SIA DCS20
- Ademco Contact ID
- 3+1 1400 Hz
- 3+1 2300 Hz
- 4+2 1400 Hz
- 4+2 2300 Hz

In addition to the DACT-E3 being compatible with digital signaling formats, the DACT-E3 features numerous formats for communication to a central station. As a digital communicator, the DACT-E3 complies with FCC Part 8, Telecommunication Standards for DC and AC Ringer Equivalence.

Installation Instructions

The DACT-E3 is adaptable for installation in standard E3 Series[®] System cabinets. Typically, the DACT-E3 module mounts on standoffs on top of the left side of the ILI-MB-E3/ILI95-MB-E3 module. Either unit can be easily connected to the backbox or sub-assembly plate depending on the cabinet module.


Note: For instructions on installing the DACT-E3, refer to the E3 Series[®] Expandable Emergency Evacuation Installation/Operation Manual, Part Number: 9020-0574 or the DACT-E3 Installation Instructions Part Number:9000-0581.

Specifications

Operating Voltage:	24 VDC (from the PM-9/PM-9G power supply)
Operating Current:	0.018 amp
Alarm Current:	0.018 amp
Operating Temperature:	32° to 120° F (0 to 49° C)
Relative Humidity:	0 to 93%, non-condensing at 90° F (32° C)

E3 Series[®] and NetSOLO[®] are registered trademarks of Honeywell International Inc.
UL[®] is a registered trademark of Underwriters Laboratories Inc.

Digital Alarm Communicator Transmitter



DACT-E3

Features

- Listed under UL[®] Standard 864, 9th Edition
- Communicates with the E3, ILI-MB-E3/ILI95-MB-E3 sub-assembly via RS-485
- Communicates in a variety of formats (including full Contact ID)
- Transmits and verifies data to the central station
- Offers pre-programmed dialing to the central station phone number
- Performs on and off-hook status to the phone lines
- Traces proper central station "ACK" and "Kiss-off" tone
- Activates hang-up and release phone lines
- Compatible with the IPDACT Internet Communicator

Ordering Information

Model	Description
DACT-E3	Digital alarm communicator transmitter

An ISO 9000-2000 Company



GAMEWELL-FCI

12 Clintonville Road, Northford, CT 06472-1610 USA • Tel: (203) 484-7161 • Fax: (203) 484-7118

Specifications are for information only, are not intended for installation purposes, and are subject to change without notice. No responsibility is assumed by Gamewell-FCI for their use.

©2010 by Honeywell International Inc. All rights reserved.

www.gamewell-fci.com

9020-0610 Rev. H page 1 of 1