



by Honeywell

Velociti[®] Series

ATD-L2F, ATD-RL2F

Description

The Gamewell-FCI Velociti[®] Series, addressable plug-in thermal sensors with integral communication provide features that surpass conventional sensors. Point ID capability allows each sensor's address to be set, providing exact locations for pinpointing alarm locations and for selective maintenance. ATD thermal sensors use an innovative thermistor sensing circuit to produce 135°F/57°C fixed-temperature (ATD-L2F). The ATD-RL2F provides a combination 15°/minute rate-of-rise with 135° fixed thermal detection that is included in a low-profile package. The ATD-HL2F provides fixed high-temperature detection at 190°F/88°C. These thermal sensors provide cost-effective, addressable property protection in a variety of applications.

The Velociti[®] Series uses a communication protocol that substantially increases the speed of communication between the sensors and Gamewell-FCI analog addressable fire alarm controls. These devices operate in a grouped fashion. If one of the devices in the group has a status change, the panel's microprocessor stops the group poll and concentrates on the single device. The net effect is response speed up to five times greater than earlier designs.

Installation

ATD plug-in sensors use a separate base to simplify installation, service, and maintenance. A special tool allows maintenance personnel to plug-in and remove sensors without using a ladder.

Mount the base on a box which is at least 1.5" (3.8 cm) deep. Suitable mounting base boxes include:

- 4.0" (10.2 cm) square box.
- 3.5" (8.9 cm) or 4.0" (10.2 cm) octagonal box.
- Single-gang box (except relay or isolator base).
- With B200SR base, mounted on a 4.0" (10.2 cm) square box.
- With B224RB or B224BI base, mounted on a 3.5" (8.9 cm) octagonal box, or a 4.0" (10.2 cm) octagonal or square box.

NOTE: Because of the inherent supervision provided by the SLC, end-of-line resistors are not required. Wiring "T-taps" or branches are permitted for Style 4 (Class "B") wiring.

Velociti[®] and E3 Series[®] are registered trademarks of Honeywell International Inc.

UL[®] is a registered trademark of Underwriters Laboratories Inc.

ULC[®] is a registered trademark of Underwriters Laboratories Canada Inc.

Addressable Thermal Sensor



ATD-L2F

Features

- Sleek, low-profile design
- Visual rotary switch addressing
- Built-in functional test switch activated by an external magnet
- Bicolor LEDs flash green whenever the sensor is addressed, and light steadily red on alarm*
- Optional relay, isolator, or sounder bases
- Low standby current
- Addressable communication
- Stable communication technique with noise immunity
- Optional remote, single-gang LED accessory (RA-400Z)
- Suitable for installation in ducts

Note: *Only the red LED is operative in panels that do not operate in Velociti[®] mode.

An ISO 9000-2000 Company

SIGNALING



LISTED
S2332



APPROVED
3023594

MEA

Approved

219-02-E Vol.VI



7270-1703:115

GAMEWELL-FCI

12 Clintonville Road, Northford, CT 06472-1610 USA • Tel: (203) 484-7161 • Fax: (203) 484-7118

Specifications are for information only, are not intended for installation purposes, and are subject to change without notice. No responsibility is assumed by Gamewell-FCI for their use.

©2009 by Honeywell International Inc. All rights reserved.

www.gamewell-fci.com

9020-0620 Rev. D page 1 of 2

Specifications

Size:	2.1" (5.3 cm) high x 4.1" (10.4 cm) diameter installed in B501 base, 6.1" (15.5 cm) diameter installed in the ADB-FLF base
Shipping Weight:	4.8 oz. (137 g)
Operating Temperature:	
ATD-L2F or ATD-RL2F	-4° F to 100° F (-20° C to 38°C)
ATD-HL2	-4° F to 150°F (-20 C to 66°C)
Sensor Spacing:	UL [®] approved for 50 ft. (15.2 m) center to center FM approved for 25 x 25 ft. (7.6 x 7.6 m) spacing
Relative Humidity:	10 – 93% (non-condensing)
ATD-L2F	Fixed-temperature setpoint 135°F (57°C)
ATD-RL2F	Combination 135° F fixed temperature and 15° (8.3°c) per minute rate-of-rise°
ATD-HL2F	Fixed-temperature setpoint 190°F (88°C)

Electrical Specifications

Voltage Range:	15 - 32 volts DC peak
Standby Current:	200 mA @ 24 VDC (without communication)
(max. avg.)	.0003 A @ 24 VDC (one communication every 5 seconds with LED enabled)
LED Current (max.)	.0065 A @ 24 VDC (LED lit)
Voltage Range	15 –32 volts DC peak

Specifications

Bases and Options

ADB-FLF	6.1" (15.5 cm) diameter standard base
B501	4.1" (10.4 cm) diameter flangeless base
B200SR	Standard Sounder base, UL [®] 864 9th Edition compliant, ULC [®] Listed
Diameter:	6.875" (17.46 cm)
B224RB	Relay Base Up to 14 AWG (2.0 mm ²) Relay type: Form-C
Rating:	2.0A @ 30 VDC resistive 0.3 A @ 110 VDC inductive 1.0 A @ 30 VDC inductive
B224RB	Relay Base
Dimensions:	6.2" (15.7 cm) x 1.2" (3.0 cm)
B224BI	Isolator Base
Dimensions:	6.2" (15.7 cm) x 1.2" (3.0 cm) Maximum 25 devices between isolator bases
RA-400Z	Remote alarm indicator, LED
BCK-200	Black detector covers (box of 10)

Ordering Information

Model	Description
ATD-L2F	Addressable thermal sensor, fixed, 135° F
ATD-RL2F	Addressable thermal sensor, combination fixed, 135° F and 15°/minute rate-of-rise.
ATD-HL2F	Addressable thermal sensor, fixed, 190° F

GAMEWELL-FCI