



by Honeywell

INCC-MIC

Description

The INCC-MIC Paging Microphone Module is a component of the NetSOLO® and E3 Series® fire alarm and voice evacuation systems.

The INCC-MIC microphone provides a cost-effective microphone interface module for paging. Installed with the ASM-16 Addressable Switch Module, it provides easy paging to selected speaker zones with visual indications of paging and zone status.

Installation

The INCC-MIC Paging Microphone Module can be installed in any of the following types of E3 Series cabinets:

- Cabinet AA
- Cabinet B
- Cabinet C
- Cabinet D

Note: Gamewell-FCI recommends that you install the speakers at 4 ft. (1.2 m) or more from the microphone.

Specifications

INCC-MIC Microphone Box	Paging Microphone Module Durable gauge steel construction with microphone holder
Dimensions:	5.5" W x 6.5" H x 2.75" D (14 W x 16.5 H x 7 D cm)

E3 Series® is a registered trademark of Honeywell International Inc.
Shure® is a registered trademark of Shure Incorporated.

Paging Microphone Module



INCC-MIC

Features

- Delivers audio feedback cancellation
- Contains a supervised microphone
- Provides status bit activation when the microphone is in use
- Offers an easy installation
- Has a preassembled microphone box with a microphone holder
- Includes a terminal block with an easy-to-use plug-in cable

Ordering Information

Part Number	Description
1100-0452	Paging Microphone Module

An ISO 9001-2000 Company

MEA
Approved
FDNY:
COA-#6077

GAMEWELL-FCI

12 Clintonville Road, Northford, CT 06472-1610 USA • Tel: (203) 484-7161 • Fax: (203) 484-7118

Specifications are for information only, are not intended for installation purposes, and are subject to change without notice. No responsibility is assumed by Gamewell-FCI for their use.

©2011 by Honeywell International Inc. All rights reserved.

www.gamewell-fci.com

9021-60402 Rev. B page 1 of 1